

SKG-IKOB PRODUCTCERTIFICATE

476.312.05

Date of issue: 12-04-2019



Certificate holder

Kale Kilit Ve Kalip A.S.
Ayazağa Mahallesi Cendere Caddesi No 109-F/1-E
34396 Sarıyer/Istanbul
T: +90 212 705 8000
E: info@kalekilit.com.tr
I: www.kalekilit.com.tr

Productielocatie

Kale Kilit Ve Kalip A.S.
Karaağaç OSB Mah. 103. Cad. No:22
59510 Kapaklı / Tekirdağ
T: +90 212 705 8000
E: info@kalekilit.com.tr
I: www.kalekilit.com.tr



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder

delivered under logo / brand:

KALE

delivered under type- and / or article number:

164 OBS

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Kale Kilit Ve Kalip A.S.
Number: 476.312.05

page 2 of 2

1. PRODUCT
euro profile cylinder

PRODUCT TYPE
cylinder

2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	double with or without escape function or single
System:	horizontal key profile 1 row of 6 mechanical operated detainers + 2 rows of 4 blocking pins
Material:	cylinder body: brass with various coatings
Dimension:	17 mm profile from 31 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length \geq backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture

3. DELIVERY

The delivery includes an installation instruction:
Version 2018-1

4. PERFORMANCES

A euro profile cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
